

DSAROUTERGSM

Router 300M Wireless 4G LTE



CARATTERISTICHE HARDWARE

- > Interfacce: 3 10/100Mbps LAN Ports, 1 10/100Mbps LAN/WAN Port,
- > 1 SIM Card Slot
- > Tasto: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
- > Dimensioni: 7.95 x 5.55 x 1.32 in. (202 x 141 x 33.6 mm)
- > Alimentatore esterno: 12V/1A
- > Tipo di antenna: 2 Internal Wi-Fi Antennas,
- > 2 External 4G LTE Antennas

CARATTERISTICHE WIRELESS

- > Standard wireless: IEEE 802.11b/g/n 2.4GHz
- > Frequenza: 2.4GHz
- > Signal rate: 300Mbps at 2.4GHz
- > Sensibilità di ricezione: 11g 54M: -71dBm
- > 11n HT20: -71dBm
- > 11n HT40: -67dBm
- > Potenza di trasmissione: CE: <20dBm(2.4GHz)
- > Funzionalità wireless: Enable/Disable Wireless Radio, WDS Bridge, WMM,
- > Wireless Statistics
- > Sicurezza wireless: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
- > Tipo di rete: 4G: FDD-LTE Cat4 (800/900/1800/2100/2600MHz)
- > TDD-LTE (2300/2600MHz)
- > 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100MHz)
- > 2G: EDGE/GPRS/GSM (850/900/1800/1900MHz)

CARATTERISTICHE SOFTWARE

- > QoS (Quality of Service): Traffic Control(IP QoS)
- > Modalità operative: 3G/4G Router, Wireless Router
- > Gestione: Access Control, Local Management, Remote Management
- > Tipo connessione WAN: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
- > DHCP: Server, Client, DHCP Client List, Address Reservation
- > Port forwarding: Virtual Server, Port Triggering, UPnP, DMZ
- > Dynamic DNS: DynDns, NO-IP
- > VPN pass-through: PPTP, L2TP, IPSec
- > Gestione accessi: Parental Control, Local Management Control, Host List,
- > Access Schedule, Rule Management
- > Firewall: DoS, SPI Firewall, IP Address Filter/Domain Filter,
- > IP and MAC Address Binding
- > Protocolli: Supports IPv4 and IPv6
- > Rete ospiti: 2.4GHz guest network x 1

ALTRO

- > Certificazione: CE, FCC, RoHS
- > Contenuto della confezione: 300Mbps Wireless N 4G LTE Router, > TL-MR6400
- > RJ45 Ethernet Cable
- > Power Adapter
- > Quick Installation Guide
- > Micro to Standard SIM Card Adapter
- > Nano to Standard SIM Card Adapter
- > z Requisiti di sistema: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1,
- > MAC OS, NetWare, UNIX or Linux

Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browsers or higher, or other Java-enabled browsers

SIM Card

Ambiente: Operating Temperature: 0~40°C; (32~104°F)

Storage Temperature: -40~70°C; (-40~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing