

# DHI-ASC2202B-D


## Access Controller



- Support TCP/IP communication;
- Two dual communication protocols: RS-485 and Wiegand (W26 and W34);
- Holds 100,000 users and stores 500,000 card swiping records;
- Support interlock, group combination, anti-passback, remote unlock, and more.
- Support card reader tamper alarm, intrusion alarm, door sensor timeout alarm, duress alarm, illegal card exceeding threshold alarm, and incorrect password alarm;
- Built-in RTC, support manual time synchronization and auto time synchronization.
- Support power-off memory protection and online upgrade;
- Support watchdog (a device that protects a system from software or hardware failures);
- Support PoE power supply.

### System Overview

The DHI-ASC2202B-D is an multi-functional access controller with a TCP/IP wired network interface. It can offer professional functions related to access control management. It is applicable to industrial parks, office buildings, financial buildings, schools, factories, CBD, residential areas, governments, and more.



### Technical Specification

#### System

Main Processor	Embedded processor
Internet Protocol	IPv4; TCP; UDP
OSDP Protocol	Yes
SDK and API	Yes

#### Basic

Product Appearance	Access Controller
Buzzer	Yes
Casing Material	PC+ABS

#### Function

Unlock Mode	Card/remote/password/fingerprint unlock
Period List	128
Holiday Period	128
Network Update	Yes
First-Card Unlock	Yes
Remote Verification	Yes
Blocklist/Allowlist	Yes

Peripheral Card Reader	4 RS-485 card readers 4 Wiegand card readers
Multi-door Interlock	Yes
Group Combination	Card/password/fingerprint unlock
Real-Time Surveillance	Yes
Multiple Authentication	Yes

#### User

User (Card) Type	General user, VIP user, patrol user, guest user, blocklist user, and other user
------------------	---

#### Capacity

User	100,000
Fingerprint	3,000
Card	100,000
Record Capacity	500,000

#### Port

RS-485 Port	5 RS-485 ports
Wiegand	4 Wiegand ports
Network	One 10/100 Mbps network port
Alarm Input	4 (digital quantity)

Alarm Output	4 (relay)
Alarm Linkage	Yes
Exit Button	2
Door Status Detection	2
Lock Control	2, normally open by default

## Alarm

Anti-Passback	Yes
Tamper	Yes
Duress	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
Duress Fingerprint	Yes


## General

Power Supply	Standard POE (support supplying power to controller and external card reader; an additional power supply for the electric lock is needed); DC 12V (support supplying power to controller, external card reader and electric lock, and 12V/0.5A is recommended for the electric lock)
IP Rating	IP20, IK04
Power Consumption	Standby 0.48W, working 14W (Standard PoE, max. 4 card readers); Standby 0.48W, working 16.8W (DC 12V, max. 4 card readers and 2 electric lock)
Product Dimensions	210 mm × 106 mm × 50 mm (8.27" × 4.17" × 1.97")
Packaging Dimensions	Packaging box: 255 mm × 166 mm × 87 mm (10.04" × 6.54" × 3.43") Protective box: 508 mm × 265 mm × 190 mm (20.0" × 10.43" × 7.48")
Operating Temperature	-30°C to +70°C (-22°F to +158°F)
Operating Humidity	5%RH–90%RH (no condensation)
Operating Altitude	0 m–1300 m (0 ft–4265.10 ft)
Operating Environment	Indoor
Gross Weight	0.6 kg (1.33 lb)
Installation	Surface/guide rail mount
Certification	CE/FCC/UL

## Ordering Information

Type	Model	Description
Access Controller	DHI-ASC2202B-D	Two-way Access Controller Model B with Two Doors (portable and indoor)

## Dimensions (mm[inch])



## Application

