

DHI-ISC-ETA2A-T301-S

AM Cable Lock T301-2A-S



Cable Lock tag is a high-performance alarming tag. Use a strong wire rope to pass through the protected goods. When the tag enters the protection mode, the wire rope will be locked, and cutting the rope will trigger a huge alarm sound and LED flash. At the same time, it also has excellent detection rate with AM anti-theft antenna. Commonly used in a variety of retail stores.

Features

Suitable for Valuable Merchandise

Strong fixation effect, can be effectively fixed on valuable goods, not easy to be damaged unless the special unlocking device is used.

High Security Protection

Breaking the tag will trigger a loud alarm tone, which can alert guards and effectively deter thieves.

Good Detection Effect

High detection rate, good anti-theft effect.

Scene

The tag can be fixed on various goods, such as clothing, shoes and hats, etc.

Technical Specification

Performance

Technology	Acousto-Magnetic (AM)
Detection Frequency	58 kHz \pm 0.5 kHz
AM Antenna Detection Distance	\leq 1.0 m (Based on system performance)
Shell Material	Acrylonitrile Butadiene Styrene (ABS)
Lock Strength	Super
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.

- Built in alarm function, triggered when tag damaged.
- High detection rate, excellent anti-theft effect.
- Small and light design, high detection performance.
- Powerful locking mechanism, effectively preventing man-made damage.
- Environmentally friendly and economical, can be reused after unlocking.

General

Alarm Sound Pressure	\geq 90 dB
Alarm Duration	5 min \pm 10 s
Low Battery Alert	Yes (When Enter Protection Mode)
Battery Model	CR2032
Battery Life	\geq 2 years
Flashing Interval	30 s \pm 2 s
Tensile Capacity	\geq 250 N
Lanyard Length	175 mm (9.84")
Lanyard Type	Metal Cable
Color	Black
Length	60 mm (2.36") \pm 0.5 mm (0.02")
Width	34 mm (1.34") \pm 0.5mm (0.02")
Thickness	16 mm (0.63") \pm 0.5 mm (0.02")
Packaging	100 Tags per Carton
Carton Dimension	380 mm \times 330 mm \times 290 mm (14.96" \times 12.99" \times 11.42")
Carton Weight	6.5 kg (14.33 lb)
Minimum Order Quantity	100 pcs

Environmental Constraints

Temperature	0 °C to 45 °C (32 °F to 113 °F)
Humidity	20 % -90 % (RH)

Ordering Information

Type	Model	Description
Alarming Tag	DHI-ISC-ETA2A-T301-S	AM Cable Lock T301-2A-S