

DHI-ISC-ETA5-T040

AM Lanyard Tag T040



The AM lanyard tag can be used together with the Acousto-Magnetic antenna to effectively prevent the theft from the goods.

Features

Suitable for Textile Products

Strong fixation effect, can be effectively fixed on clothes and other items, not easy to be damaged unless the special unlocking device is used.

High Reuse Rate

High reuse rate after recycling.

Good Detection Effect

High detection rate, good anti-theft effect.

Scene

The tag can be fixed on various goods, such as clothing, shoes and hats, etc.

Technical Specification

Performance

| | |
|-------------------------------|--|
| Technology | Acousto-Magnetic (AM) |
| Detection Frequency | 58 kHz \pm 0.5 kHz |
| AM Antenna Detection Distance | \leq 1.0 m (Based on system performance) |
| Shell Material | High Impact Polystyrene |
| Lock Strength | Standard |
| Certifications | Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments. |

General

| | |
|--------|------------------------------------|
| Color | Gray |
| Length | 53 mm (2.09") \pm 0.5 mm (0.02") |

- Environmentally friendly and economical, can be reused after unlocking.
- Small and light design, high detection performance.
- High detection rate, excellent anti-theft effect.
- Lower labor operating costs, widely applicable in merchandising shops.
- Powerful locking mechanism, effectively preventing man-made damage.

| | |
|------------------------|---|
| Width | 13 mm (0.51") \pm 0.5 mm (0.02") |
| Label Thickness | 24 mm (0.94") \pm 0.5 mm (0.02") |
| Lanyard Length | 100 mm (3.94") |
| Lanyard Type | Metal Cable |
| Packaging | 1000 AM Tags per carton |
| Carton Dimension | 400 mm \times 300 mm \times 190 mm (15.75" \times 11.81" \times 7.48") |
| Carton Weight | 8.5 kg (18.7 lb) |
| Minimum Order Quantity | 1000 pcs |

Environmental Constraints

| | |
|-------------|---|
| Temperature | Maximum storage temperature not to exceed 60 °C for 96 hours at 80% RH. |
| Humidity | Maximum storage humidity not to exceed 80% RH for 96 hours at 60 °C. |

Ordering Information

| Type | Model | Description |
|--------|-------------------|---------------------|
| AM Tag | DHI-ISC-ETA5-T040 | AM Lanyard Tag T040 |