

DHI-ISC-ET-P001

Flat Steel Pin



- Environmentally friendly and economical, can be reused after unlocking.
- Small and light design, great-looking.
- Lower labor operating costs, widely applicable in merchandising shops.

System Overview

The pin is an accessory of EAS label, with solid structure and anti-rust treatment. It can prevent EAS tag from being forcibly removed. Smooth pin can reduce damage to goods, slot pin can improve the level of protection.

Features

Suitable for EAS Tags

Strong fixation effect, can be effectively fixed on clothing, use with EAS tags.

High Reuse Rate

High reuse rate after recycling.

Multiple Types Available

Both smooth and slot type can be selected according to customer needs.

Scene

The pin can be fixed on various EAS tags.

Attention

There is a risk of breaking and stabbing, do not knock, do not give it to children.

Technical Specification

Performance Parameters

Shell Material	Stainless Steel	
Pin Material	Stainless Steel	
Pin Type	Smooth	Slot
Certifications	Conform with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulations as defined in EC No 1907/2006 and subsequent amendments.	

General parameters

Width	10.5 mm (0.41") ± 0.5 mm (0.02")
Thickness	10.5 mm (0.41") ± 0.5 mm (0.02")

Pin Length	16 mm (0.63") ± 0.5 mm (0.02")
Packaging	1000 pin per box, 20 boxes per carton
Inner Box Dimension	117 mm × 110 mm × 60 mm (4.61" × 4.33" × 2.36")
Inner Box Weight	1.0 kg (2.20 lb)
Carton Dimension	465 mm × 315 mm × 135 mm (18.31" × 12.40" × 5.31")
Carton Weight	20.5 kg (45.19 lb)
Minimum Order Quantity	1 box

Environmental Constraints

Temperature	0 °C to 50 °C (32 °F to +122 °F)
Humidity	10 % - 90 % (RH)

Ordering Information

Type	Model	Description
EAS Pin	DHI-ISC-ET-P001A	Flat Steel Pin Smooth
EAS Pin	DHI-ISC-ET-P001B	Flat Steel Pin Slot