

CCP-W/IS

Intrinsically Safe Weatherproof Conventional Call Point

Features

- ▶ Sealed to IP67
- ▶ Supports either a 'Frangible' glass element or a 'Non Frangible' plastic element
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Approved to EN54 Part 11
- ▶ Rugged design, with anti-tamper facility
- ▶ ATEX Classification to II 1GD Ex ia IIC T4 Ga
- ▶ SIL Level 2 approved variant available.



Description

The CCP-W-IS is a conventional weatherproof call point based upon the industry standard KAC world series housing, and which can be used externally in hazardous areas.

IMPORTANT NOTE: If changing the element from Glass to Flexi, please confirm the operation by pressing the resettable element.

Specification

Ordering Code	CCP-W/IS
Operating Voltage	15 – 30 VDC
Operating Temperature Range	- 25 °C to + 75 °C
Storage Temperature Range	- 25 °C to + 75 °C
ATEX Classification	II 1 G Eex ia II T4 ga
Maximum Humidity	93% RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP67
Colour / Case Material	Red / Polyphenylene Oxide
Weight (g) / Dimensions (mm)	350 / W 97.5 x H 93 x D 71



For further information visit our website. Hochiki reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki to be a complete and up-to-date description. Check online for current version.

