



Smoke Sensor for SEC-ASD-531

SEC-SSD-31 Alarm Sensitivity range
0,02% – 10% /m

The smoke sensor SSD 31 is pre-installed in the SEC-ASD-531 and is also available also as replacement part. 3 Pre-signals are set on a fixed percentage of the alarm threshold (30/50/70%).

Technical data

| | |
|--------------------------------|-------------------|
| Sensitivity range alarm: | 0.02 %/m – 10 %/m |
| Sensitivity range pre-signals: | 0.006 %/m – 7 %/m |
| Ambient temperature: | -10 °C to + 55 °C |
| Dimensions (H x W x D): | 120 x 116 x 95 mm |



Smoke Sensor for SEC-ASD-532

SEC-SSD-532-3 Alarm Sensitivity range
0.02% – 10% /m

The smoke sensor SSD 532 has to be ordered separately for the SEC-ASD-532. 3 Pre-signals can be set between 10 and 90% of the alarm threshold.

Technical data

| | |
|--------------------------------|-------------------|
| Sensitivity range alarm: | 0.02 %/m – 10 %/m |
| Sensitivity range pre-signals: | 0.002 %/m – 9 %/m |
| Ambient temperature: | -20 °C to + 60 °C |
| Dimensions (H x W x D): | 120 x 116 x 95 mm |



Smoke Sensor for SEC-ASD-535

SEC-SSD-535-3 Alarm Sensitivity range
0.02 – 10% /m

The smoke sensor SSD 535 has to be ordered separately for the SEC-ASD-535. Pre-signals can be set between 10 and 90% of the alarm threshold.

Technical data

| | |
|--------------------------------|-------------------|
| Sensitivity alarm: | 0.02 %/m – 10 %/m |
| Sensitivity range pre-signals: | 0.002 %/m – 9 %/m |
| Ambient temperature: | -30 °C to + 60 °C |
| Dimensions (H x W x D): | 120 x 136 x 95 mm |