

## DHI-ARM9A4-P-W2(868) Info

<b>Technical Specification</b>	
<b>Port</b>	
Network Port	1 × RJ-45 10 M/100 M Ethernet port
Serial Port	1 (Reserved)
Power supply port	1 (100~240V)
Battery port	1 × 12V DC input
Power switch	1
Alarm input	16 (NO/NC with Non/1EOL/2EOL/3EOL, Resistance value:1.1/2.2/4.7/5.6/6.8/8.2/Customization(1-15 )KΩ), 1-6 supports pulse detection
Alarm output	4 (NO/NC, AC125V/1A/DC30V3A)
Auxiliary power output	2 (14.5V, total 0.75A when powered by POE, total 2A when powered by AC)
Indicator Light	1 for multiple status
Tamper-proof	2, Front and rear
Reset button	1
<b>Electrical Characteristics</b>	
Power supply	100-240VAC, POE(802.3at), Battery
Battery type	Compatible with 12v 7 Ah
Battery life Span	Up to 30 Hours
<b>Wireless Transmission</b>	
RF frequency	868 MHz/433 MHz
RF mechanism	Two-way communication
RF modulation	2GFSK
RF distance	1600m
<b>General</b>	
Shell material	Plastic
Color	White
Product dimensions	304*235*90.8mm
Net weight	1287g
Certification	CE

